



Model No.	Bearing	Voltage	Frequency	Current	Input Power	Speed	Air Flow	Static Pressure	Noise
	○ Sleeve ● Ball	VAC	Hz	A	W	RPM	CFM	mm H ₂ O	dB(A)

Aluminium Housing with Plastic Impeller

3" 80 x 80 x 25 mm | 3-1/8 x 3-1/8 x 1 in



EC - 8025 A1 W	○	115	50/60	0.04	2.4	3000	27	4.5	30
EC - 8025 B1 W	●	115	50/60	0.04	2.4	3200	29	4.5	32
EC - 8025 A2 W	○	230	50/60	0.02	2.4	3000	27	4.5	30
EC - 8025 B2 W	●	230	50/60	0.02	2.4	3200	29	4.5	32

4" 120 x 120 x 38 mm | 4-11/16 x 4-11/16 x 1-1/2 in



Note : High Speed RPM Also Available

EC - 12038 A1 T	○	115	50/60	0.07	6.5	2650	100	7	43
EC - 12038 B1 T	●	115	50/60	0.07	6.5	2750	105	7.4	43
EC - 12038 A1 W	○	115	50/60	0.07	6.5	2650	100	7	43
EC - 12038 B1 W	●	115	50/60	0.07	6.5	2750	105	7.4	43
EC - 12038 A2 T	○	230	50/60	0.07	6.5	2650	100	7	43
EC - 12038 B2 T	●	230	50/60	0.07	6.5	2750	105	7.4	43
EC - 12038 A2 W	○	230	50/60	0.07	6.5	2650	100	7	43
EC - 12038 B2 W	●	230	50/60	0.07	6.5	2750	105	7.4	43



6" Ø172 x 150 x 51 mm | 6-3/4 x 5-7/8 x 2 in

Note : High Speed RPM Also Available

EC - 17251 A1 W	○	115	50/60	0.14	10	2600	160	13	55
EC - 17251 B1 W	●	115	50/60	0.14	10	2700	170	13	57
EC - 17251 A2 W	○	230	50/60	0.11	12	2600	160	13	55
EC - 17251 B2 W	●	230	50/60	0.11	12	2700	170	13	57



8" Ø220 x 60 mm | Ø 8-21/32 x 2-3/8 in

Note : High Speed RPM Also Available

EC - 22060 R B1 W	●	115	50/60	0.22	18	2250	405	24	62
EC - 22060 R B2 W	●	230	50/60	0.17	22	2500	405	24	62

Plastic Housing with Plastic Impeller



4" 120 x 120 x 38 mm | 4-11/16 x 4-11/16 x 1-1/2 in

Note : High Speed RPM Also Available

EC - 12038 A1 W	○	115	50/60	0.07	6.5	2650	100	7	43
EC - 12038 B1 W	●	115	50/60	0.07	6.5	2750	105	7.4	43
EC - 12038 A2 W	○	230	50/60	0.07	6.5	2750	105	7	43
EC - 12038 B2 W	●	230	50/60	0.07	6.5	2800	110	7.4	43

Note : Terminal Fan Also Available